



## High Definition Audio

LifeSize® Phone™ is the High Definition audio conference phone that delivers a revolutionary level of quality to audio conferencing.

Better Input. Powered by 16 always-on microphones and patent-pending Circular Microphone Array™ and beam forming technology, LifeSize Phone provides exceptional room coverage over other phones.

**Expand the coverage so everyone can be heard**

Better Algorithms. True CD quality, super wide-band audio operates up to 16 kHz frequency using MPEG-4 AAC, the same algorithm used in the popular iPod® and iTunes® products.

Better Output. Using a specially designed titanium speaker driver and tuned ported enclosure, LifeSize Phone reduces unwanted noise and distortion by up to 10X over any other conference phone—and no need for a subwoofer.

Flexible Connectivity. LifeSize Phone provides Voice over IP (VoIP) audio conferencing and integration to a host of Enterprise-class IP-PBX systems. Also, use LifeSize Phone as a fully integrated audio solution with LifeSize® Room™ and LifeSize® Team™ video systems.

Hear and understand everyone. No more conference fatigue. LifeSize Phone sets the new standard in productive conferencing. Clearly.

## The Advantages are Clear

**Complete Room Coverage** — Pick up all talkers in the room without unwanted noise. Innovative design with 16 omnidirectional microphones and exclusive Circular Microphone Array provides a superior approach to gated, directional microphone devices

**Super Wide-Band, Up to 16 kHz Audio** — World's best frequency response from 100 Hz up to 16 kHz for highly intelligible conferencing

**Standards Compliant** — Works with standard SIP or H.323 IP PBX or IP service provider implementation

**Low Distortion and Ambient Noise** — Designed to reduce noise from HVAC, projector fans for sensitive microphone or talker pickup without the noise

**Elegant, Non-Intrusive Design** — Updated design and no additional microphone pods or sub woofers required.

**Simple to Use** — Intuitive keypad and display, add a third participant at the touch of a button

**Investment Projection** — Software-based, remotely upgradable device.

# Product Specifications

## Phone Console Specifications

### System Speaker

Specially designed titanium speaker driver  
¼ liter tuned ported speaker enclosure  
Typical frequency response: 100 Hz to 16 kHz  
for stand alone phone with IP connection

Distortion:

<0.5% 400 Hz - 20 kHz

<2% 100 Hz - 400 Hz

Volume: adjustable to 90dBA spl @ .5m

No sub-woofer required

### System Microphones

Circular Microphone Array with 16 embedded microphones and beam forming with Directivity Index (DI) greater than 4 for all audio frequencies  
No microphone pods required

### Display

Large monochromatic LCD display  
240 x 64 pixels; .250 mm pitch



### Keypad

Intuitive keypad

### Network

VoIP connectivity or video systems integration in one device

### Audio Standards

G.711; G.722; G.722.1c (Polycom® Siren14™); G.729;  
MPEG-4 AAC  
SIP: RFC 3261; 3264; 2833

## Network Configuration Options

IP Configurations

Standard SIP or H.323 IP PBX or IP service provider implementation

To access supported implementations:  
[www.lifesize.com/support](http://www.lifesize.com/support)



### QoS

Packet loss concealment  
Jitter buffer granularity of 1ms  
AEC echo tail of >100 ms

### No Mobile Phone or PDA Interference

Designed to reduce or eliminates radio frequency interference when placed adjacent to LifeSize Phone

### Systems Management & Maintenance

Web browser management for setup and usage  
Inventory and remote management using SNMPv3  
LifeSize® Control™ management software on IP network



## System Design

Physical Dimensions

Height: 40.89 mm / 1.61 in

Diameter: 286.29 mm / 11.27 in

Weight: 1.34 Kg / 3 lbs

## Environmental Data

Operating temperature:

0°C (32°F) to 40°C (104°F)

Operating humidity:

10% to 85%, non-condensing

Storage temperature:

-40°C (-40°F) to 70°C (158°F)

Storage humidity: 10% to 90%

## LifeSize Phone Package

Tabletop console

Quick start guide

Cables:

1-30 ft. (9.14m) RJ-45 cable to Speakerphone Console

Power over Ethernet (PoE) enabled, 802.3af

PoE Adapter not included. For recommendations, visit:  
[www.lifesize.com/support](http://www.lifesize.com/support)

LifeSize Phone is available worldwide in multiple languages.

For additional information: [www.ipl.com.au](http://www.ipl.com.au)

Information contained in this document is subject to change without notice. LifeSize is a registered trademark or trademark of LifeSize Communications in the U.S. and other countries. All other trademarks are property of their respective owners. Copyright 2007. May 2007.



Connecting  
with people

IPL Communications  
146 O'Riordan St  
MASCOT, NSW, 2020  
+61 2 9667 7000  
[onlineorders@ipl.com.au](mailto:onlineorders@ipl.com.au)